

Dual color medium intensity OFP-360-RW-JB P/N 113731JB and complete remote power supply OFP-CAB-1B-RW-240-4M32-S P/N 114111

Flash-head

- ✦ 6 led projectors in aluminium and glass
- ✦ 2 white led circuits and a red with infrared circuit inside each projector
- ✦ NVG visible
- ✦ Simple installation with no losing parts when opening the flash-head

Full remote power supply




- ✦ 'Weather tight' stainless steel 316L power cabinet enclosure
- ✦ Test button with 3 positions: remote (photocell), day and night mode
- ✦ Normally open or normally close relay in case of lamp default or power supply
- ✦ Communication capabilities (controller, Modbus TCP)
- ✦ Test button for day and night
- ✦ Luminous indicators for quick diagnostic
- ✦ Surge protection with indicator showing when it has failed included
- ✦ GPS controlled or in back-up activated in case of failure or absence of an external high intensity controller or photocell
- ✦ Alarm in compliance with FAA Engineering Brief 98
- ✦ Multi-layer of surge protections



1966535B1 & US 7816843

Patents: EP

Les dimensions sont en mm
All dimensions are in mm



Electrical Characteristics	
Main voltage	110VAC to 240VAC +/-10% 50/60Hz
Average wattage	55W (day time), 8W (night mode)
Mechanical Characteristics	
IP degree	IP66 per projector
Wiring	Entry of cable by glands nickel plated brass and connection by terminals
Operating temperature	-40/+55°C
Size of the light	333mm (height) x 500mm (diameter)
Size of the power supply	400mm (height) x 300mm (width) x 200mm (dept)
Weight	18kg for flashhead, 10kg for power cabinet
Wire cross section	from 1 to 4 mm ²
Attachment	6 mounting holes dia.16mm, dia.337mm circle (FAA standard)
Photometric Characteristics	
Effective light output day time at 0° on site	20 000cd (white)
Effective light output twilight mode at 0° on site	20 000cd (white)
Effective light output night mode at 0° on site	2000cd (red) with IR
Color day/twilight time	white
Color night time	Red
Vertical beam spread	>3°
Horizontal beam spread	360°
Flash per minute	20, 30, 40 or 60 flashes per minute
Standards	
Standards compliance	ICAO annex 14 chapter 6, FAA (AC 150/5345-43J), UK MOD, Transport Canada
Certification	FAA (AC 150/5345-43J), ETL listed, DGAC(Fr)