


Cold neon discharge low intensity type B



- Perfectly waterproof with hard glass cover
- Not sensitive to temperature
- Great light efficiency
- ▸ Large vertical beam spread exceeding FAA and ICAO standard
- > EMC re-enforced with grounding,
- Protected against transient overvoltages
- ▶ Alarm by closing relay in case of lamp failure or low power supplyy



Câble: L= Im env.	4 x 1.5 mm ²	L
NOTE: Washers and screws forwall fixation are not supplied. Marking Screw M6 Lock washer	Clamp the harness screws	LCV
4 8 12 16 20 24 28 32 36	90*	

Electrical Characteristics	
Wattage	45 W
Current drawn	370mA(240V) - 730 mA(110V)
Life time	~10years
Main voltage	110VAC to 240VAC +/-10% 50/60Hz
Mechanical Characteristics	
IP degree	IP66
Wiring	On 5 stripped wires (cable lenght 1 meter) (2 power wires 2x1,5mm², 2 alarm wires 2x1,5mm² and 1 ground wire 2,5mm²)
Operating temperature	-40/+55°C
Weight	2.6 kg
Size of the light	600mm (height) x 68mm (over diameter)
Weight	2,3 kg
Attachment	2 screws type M8 (provided). Thikness to screw into : 1 up to 5 mm
Photometric Characteristics	
Luminous intensity	> 32,5 Cd
Color night time	Red fixed
Vertical beam spread	>120°
Horizontal beam spread	360°
Standards	
Standards compliance	ICAO annex 14 chapter 6, FAA AC 150/5345-43G