




This OBSTAFLASH120 ou 180 dual color medium intensity type A and B (or C) is designed for day and night marking of obstacle such as chimneys, pylons and high rise buildings (3 or more lights are required per level depending on diameter of the obstacle)

The flashhead includes

- ▶ 2 projectors in glass and aluminium painted with 75cm of molded cable and connector
- ▶ a junction box OGP-JB-6P-RW-L for 6 projectors and the connector of the power supply cable 113762
- Stainless support for the 2 projectors and the junction box



EP3230651, FR1462349, Pat. 10,247,386



| Mechanical Characteristics | |
|--|---|
| Wiring | Connectors L |
| Operating temperature | -40/+55°C |
| Weight | 4.5 kg |
| Size of the light | 120mm (height) x 480mm (width) |
| Weight | 3,5kg |
| Photometric Characteristics | |
| Effective light output day time at 0° on site | 20 000cd (white) |
| Effective light output twilight mode at 0° on site | 20 000cd (white) |
| Effective light output night mode at 0° on site | 2000cd (red) with IR |
| Color day/twilight time | white |
| Color night time | Red or white |
| Vertical beam spread | >3° |
| Horizontal beam spread | 360° with minimum 3 flashheads fixed at 120° around the obstacle |
| Standards | |
| Standards compliance | ICAO annexe 14 chapter 6 (8th edition 07/2018), EASA (4th edition 2017) |