

The Bird Diverter Spiral is designed to make overhead lines visible to birds and provides an economic means of reducing the hazard to both lines and birds. It can be installed on conductors up to 132KV, guard cables, guyes structures visible to birds and for high voltages, it is

The Bird diverter spiral offers little wind resistance and is easily and quickly applied by hand or by hot stick. The positive grip of the fitting on the conductor ensures that it remains in the applied position and cannot move along the span under aeolian vibration or other conditions.

Color and diameter of the cable to be specified at time order as per table below

- ✦ Made in PVC shockproof with UV protection
- ✦ Low weight
- ✦ Quick installation with no losing part
- ✦ Good grip in the cable
- ✦ Long lifetime
- ✦ Wind resistant




Table 1: Bird diverter spiral (BDS)

P/N*	Min. (mm)	Max. (mm)	Length (mm)	Rad Dia. (mm)
100935-4464X	4.44	6.4	400	9.5
100935-6389X	6.35	8.9	400	9.5
100935-89114X	8.9	11.4	400	9.5
100935-114152X	11.43	15.21	400	9.5
100935-152195X	15.2	19.56	400	9.5
100935-195217X	19.56	21.79	400	12.7
100935-218239X	21.80	23.92	400	12.7
100935-239248X	23.93	24.85	400	12.7

*Final designation and part number to be confirmed at order time.
*Replace X to W/R/O or Y depending on the required color. Contact us for other range diameters or colors.

Mechanical Characteristics

Cable diameter	Ø 12.60mm to 26.40mm
Color	white, red, orange or yellow
Weight	0.22kg