

NAVILITE-IR-F-048-KIT [P/N: 113965IR-KIT]


Red light FAA L-810 as per FAA (AC 150/5345-43J)



- L-810 type red fixed with IR emissions (or L-810 (F) mimic with L-864 medium intensity) depending on internal switches positions
- ▸ ICAO low intensity type A B or E with IR depending on internal switches positions
- ▶ Light part fully molded with 8 levels of leds
- Redundant circuits for LED's with de-coupled IR
- Surge protection and alarm included
- normally open and normally close both available for the alarm complying with FAA Engineering Brief 98
- > monobloc design with no loose part during installation
- Built-in flasher (activated through dip-switches with master/slave possibility) to mimic with L-864 medium intensity P/N113790RI-240, P/N113756U & P/N113714U or dual color L-865/L-864 medium intensity P/N113725UI, P/N113715U & P/N113758U,

Provided with stainless bracket for mounting and hot-galvanized cable entry

Option with IR (visible with Night Vision Goggles as per FAA Advisor 150/5345-43J)



Electrical Characteristics	
Life time	~10years
Main voltage	20-60Vdc
Average wattage	8W (steady mode) or 2W (@ 30 fpm mimic with L-864)
Mechanical Characteristics	
IP degree	IP66
Wiring	Terminal connection (2 power wires and 2 for the alarm)
Operating temperature	-40/+55°C
Weight	2.5 kg
Wire cross section	from 1 to 2,5 mm ²
Attachment	2 NPT threaded holes
Photometric Characteristics	
IR intensity and wavelength	25mW/sr @ 850nm
Luminous intensity	> 32,5 Cd
Color night time	Red
Vertical beam spread	>10°
Horizontal beam spread	360°
Standards	
Standards compliance	ICAO annex 14 chapter 6, FAA (AC 150/5345-43J), UK MOD, Transport Canada