OFC-RI-240 [P/N: 113790RI-240]


Red medium intensity FAA L-864 (AC 150/5345-43J) ETL certified




Patents: **EP 1966535B1 & US 7816843**

Flash-head with integrated power supply

- 6 Obsta optics with cover in hard glass and aluminium base
- Simple installation with no losing parts when opening the flash-head
- Power supply inside the flash-head
- NVG compatible (with IR)
- Alarm in compliance with FAA Engineering Brief 98
- Surge protection with indicator showing when it has failed included
- membrane vent
- Top sync for optional side lights L-810(L)(F) NAVILITE-IR-FAA-120-240V P/N113969IR-F
- GPS antenna included, internal photocensor "-R" in option
- Choice of the configurations (ICAO medium intensity type B (20, 30, 40, 50 ou 60 flashes per minute) or ICAO medium intensity type C (steady mode) or FAA L-864 and L-885) done through dip-switches inside the light, to be specified at time order. FAA configurations L-864 and L-885 must be ordered with suffix L864 and L865





Electrical Characteristics	
Main voltage	110VAC to 240VAC +/-10% 50/60Hz
Average wattage	7W (ICAO and FAA configuration @ 30 flashes per minute)
Mechanical Characteristics	
IP degree	IP 66
Wiring	Entry of cable by glands nickel plated brass and connection by terminals
Operating temperature	-40/+55°C
Weight	5kg
Size of the light	220mm x 190mm x 190mm
Cable entry diameter	from 7 to 13 mm
Wire cross section	up to 6mm² for power supply, up to 1,5mm² for signal
Attachment	4 mounting holes dia.9mm, 200mm x 140mm
Photometric Characteristics	
IR intensity and wavelength	> 600mW/sr @ 800-900nm
Effective light output night mode at 0° on site	2000cd (red or white)
Color night time	Red or white
Vertical beam spread	>3°
Horizontal beam spread	360°
Flash per minute	30
Standards	
Standards compliance	ICAO annex 14 chapter 6, FAA (AC 150/5345-43J), UK MOD, Transport Canada
Certification	FAA (AC 150/5345-43J), ETL certified, DGAC(Fr)